

AT500

Magnetostrictive Level Transmitter

Compact magnetostrictive
liquid level transmitter for direct
insertion

K-TEK Products



Features

- Mounts from Top of Tank
- High Resolution 4-20 mA Output
- Simple Mounting and installation
- Very Compact Design
- Calibrates Without Opening Enclosure
- Stainless Steel Enclosure
- Custom Floats Available
- Measurement of Total or Interface Level


SPECIFICATIONS

Electronic Transmitter

Repeatability	.01% of full scale or 0.030", whichever is greater
Non-linearity	.02% of full scale or .07", whichever is greater
Accuracy	.02% of full scale or .10", whichever is greater
Loop Supply Voltage	13.5 to 36 VDC
Housing Type	Explosion proof 316L SS with 1/2" FNPT Electrical Connection
Polarity Protection	Diode in series with loop
Output	Standard 4-20 mA
Failsafe	Calibration via magnets Field Selectable: Upscale or Downscale
Operating Temperature	Electronics -40 to 170°F (-40 to 77°C) Ambient
Humidity	0-100% R.H. non-condensing
Electrical Connection	1/2" FNPT Standard; M20 Optional
Enclosure Rating	IP67

Sensor Tube

Material	316/316L Stainless Steel, 5/8" OD
Operating Temperature	-40 to 170°F / -40 to 77°C Standard Up to 250°F / 121°C with 10" extension (H1)
Max Pressure	1800 psig @ 250°F Standard 124.1 bar @ 121°C Standard
Measuring Range	1 to 16 ft. / 0.3 to 4.8 m
Mounting	Standard 3/4" MNPT compression fitting (refer to ordering information for options)



AT500 Sample Applications
Total and Interface Measure-
ment

Approvals



Factory Mutual Research Corporation:

XP/II/1/ABCD/T6 Ta=77°C; I/1/AEx d IIC/T6 Ta=77°C;

DIP / II ,III / 1 / EFG / T6 Ta=77°C

IS/II/1/ABCD/T4 Ta=77°C; I/0/AEx ia IIC/T4 Ta=77°C-ELE 0035/NC; Entity;

NI/II/2/ABCD/T4 Ta=77°C; S/II,III/2/FG/T5 Ta=77°C; NEMA 4X



CSA International:

Hazardous Locations

Class I, Div. 1, Grps A,B,C,D; Class II, Div. 1, Grps E,F,G; Class III;

Class I, Zone 1, Ex d, IIC T6:



Intrinsically Safe Entity - For Hazardous Locations:

Class I, Div. 1, Grps A,B,C,D, Temp. Code T4;

Class I, Zone 0, Ex ia IIC T4 when installed per drawing ELE0035,

Max. operating temp. 77°C, Encl. Type 4X.

ATEX:

Flameproof: EX II 1/2 GD T85C EEx d IIC T6

Intrinsically Safe: EX II 1 GD T85C EEX ia IIC T6



GOST Russia, GOST Kazakhstan: 1ExdIICT6, 0ExiaIICT6, IP67



AAR Association of American Railroad Certification with FM Approval:

E069022


Safety



Third Party Safety Integrity Level (SIL) data (FMEDA analysis) for Safety Instrument Systems engineering is available.

PRINCIPLE OF OPERATION

The AT500 is based upon the magnetostrictive principle. The sensing tube contains a wire which is pulsed at fixed time intervals. The interaction of the current pulse with the magnetic field created by the magnetic float causes a torsional stress wave to be induced in the wire. This torsion propagates along the wire at a known velocity, from the position of the magnetic float and toward both ends of the wire. A patented piezo-magnetic sensing element placed in the transmitter assembly converts the received mechanical torsion into an electrical return pulse. The microprocessor-based electronics measures the elapsed time between the start and return pulses and converts it into a 4-20 mA output which is proportional to the level being measured.



ORDERING INFORMATION

AT500/a/b/c/d/e/f/g/h/i/j:

/a	Probe Material	
	S6	316L Stainless Steel Standard
/b	Transmitter configuration	
	L	Local Transmitter Standard
/c	Transmitter Housing	
	S	316L Stainless Steel Housing Standard
/d	Probe Type	
	R1	Rigid Probe 5/8 in. O.D. (16 ft./ 4.87m maximum probe length) Standard
	SW1	1/2" OD Probe for Insertion into 5/8" OD x 0.049" Wall Sensor Well Note: Specify and order sensor well separately.
	SW2	5/8" OD Probe for Insertion into 3/4" Sch. 40 or Sch. 80 Sensor Well Note: Specify and order sensor well separately.
/e	Process Temperature Options	
	H0	170°F / 77°C Maximum Standard
	H1	250°F / 121°C. Maximum (Top of transmitter is 17 in. / 43 cm above tank nozzle)
/f	Electrical Connection	
	F5	1/2 in. FNPT Standard
/g	Approvals	
	FM	Factory Mutual and CSA Canadian Standard Association
	CEI	ATEX Intrinsically Safe
	CEX	ATEX Flameproof
	GR	GOST Russia
	AAR	AAR Association of American Railroad Certification with FM Approval
	M2	M20 Connection
	RF	RFI Filter with 1/2 in. MNPT connection and flying leads



/h	Process Connection												
	CF	3/4 in. MNPT x adjustable compression fitting Standard											
	FL	Flange with 3/4 in. NPT tap shipped loose; Specify from Flange Selection chart (SLG-0001-1).											
/i	Float Type												
	Fnn	Selection from Standard Float Chart (SLG-0003-1) F1B, F2B, F17B, F15B Standard or specify /FXX for custom float											
/j	Length												
	L	<p>Standard lengths:</p> <table> <tr> <td>15.5 in. / 394 mm</td><td>27.5 in. / 698 mm</td><td>39.5 in. / 1003 mm</td></tr> <tr> <td>51.5 in. / 1308 mm</td><td>63.5 in. / 1613 mm</td><td>75.5 in. / 1918 mm</td></tr> <tr> <td>87.5 in. / 2222 mm</td><td>99.5 in. / 2527 mm</td><td>111.5 in. / 2832 mm</td></tr> <tr> <td>123.5 in. / 3137 mm</td><td>135.5 in. / 3442 mm</td><td>147.5 in. / 3746 mm</td></tr> </table> <p>Custom Lengths to 16 ft. / 4876 mm specified in inches or millimeters</p>	15.5 in. / 394 mm	27.5 in. / 698 mm	39.5 in. / 1003 mm	51.5 in. / 1308 mm	63.5 in. / 1613 mm	75.5 in. / 1918 mm	87.5 in. / 2222 mm	99.5 in. / 2527 mm	111.5 in. / 2832 mm	123.5 in. / 3137 mm	135.5 in. / 3442 mm
15.5 in. / 394 mm	27.5 in. / 698 mm	39.5 in. / 1003 mm											
51.5 in. / 1308 mm	63.5 in. / 1613 mm	75.5 in. / 1918 mm											
87.5 in. / 2222 mm	99.5 in. / 2527 mm	111.5 in. / 2832 mm											
123.5 in. / 3137 mm	135.5 in. / 3442 mm	147.5 in. / 3746 mm											
<u>Available Accessories</u>													
	CD	Centering Disk: specify stilling well inside diameter											
	M20 ISO FITTING	M20 Connection											
	CONHEA4F	3 pin female cable connector with weatherproof cap rated for general purpose & intrinsically applications only.											
	CONHEA4M	3 pin male cable connector with weatherproof cap rated for customers cable at loading station. General purpose & intrinsically safe applications only.											

Contact us

ABB Inc.

18321 Swamp Road
Prairieville, LA 70769 USA
Phone: +1 225 673 6100
Service: +1 225 677 5836
Fax: +1 225 673 2525
Service e-mail: service@us.abb.com

www.abb.com/level

Note

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents - in whole or in parts - is forbidden without prior written consent of ABB.

Copyright© 2012 ABB
All rights reserved

DS/AT100-EN Rev. A 06.2012